



# Geo 7 Series

## HANDHELD

### READY FOR ANYTHING

The Trimble® Geo 7X handheld is from the Trimble GeoExplorer® series family of integrated, rugged, and high-accuracy GNSS handhelds. As a streamlined solution that enables faster and more productive data collection, the Geo 7X is ideal for organizations, such as utility companies, municipalities, and environmental agencies, requiring mobile data collection and asset management solutions.

#### Eliminate Physical Barriers to Field Success

When physically occupying a position is not possible due to dangerous conditions or right-of-way challenges, turn to Trimble Flightwave™ technology integrated in the Geo 7X. Utilizing the detachable Geo 7 rangefinder accessory, Flightwave workflows enable scale and location measurement of field assets at distances up to 120 m without a reflector. Flightwave measurements integrate directly into Trimble data collection software—simply point and shoot to get the position—even where there are obstacles such as traffic or private land access limitations.

Trimble Floodlight™ satellite shadow reduction technology keeps you working when heavy overhead cover, such as trees and buildings, obstruct GNSS satellite reception. Now you can work with fewer disruptions and obtain high quality data faster and at less cost.

#### Smart Data Collection, Smart Investment

By providing compatibility with existing and currently planned GNSS constellations, the Geo 7X delivers reliable GNSS tracking today and for years to come—ensuring your investment continues to provide value long into the future.

Achieve better accuracy in real-time without the reliance of a traditional reference station-based infrastructure or VRS network through Trimble RTX™ correction service options available with the Trimble Geo 7X. Trimble RTX correction services leverage real-time data from an established tracking station network to compute and deliver high-accuracy positions to the GNSS handheld nearly anywhere on the globe. A range of Trimble RTX correction services offered with the Trimble Geo 7X provide internet-delivered, high-accuracy GNSS positioning wherever cellular communications are available so you can obtain the accuracy you need—from submeter to centimeter level.

Compatible with the breadth of Trimble GIS field and office software, the Geo 7X gives you flexible end-to-end data collection solutions and workflow choices: from the field-proven Trimble TerraSync™ and Positions™ software to the customizable data collection workflows of Trimble TerraFlex™ software.

#### Everything You Need to Work

With a powerful 1.0 GHz processor, 256 MB RAM, 4 GB of onboard storage, IP65 rating, and sunlight-optimized display, the Geo 7X is a high performance device designed to work hard in the environments that you do. The built-in 5 MP camera with enhanced zoom operation, and geo-tagging capability enables information about an asset, event, or site to be easily captured. And with the integrated dual-mode cellular modem, you can stay connected for continuous network and Internet access to real-time map data, web-based services, Trimble VRS™ and RTX corrections, and live update of field information.

Be truly productive with the Trimble Geo 7 series. No matter what gets in your way.

### Key Features

- ▶ Easy and productive asset data capture with remote mapping and measurement
- ▶ Capture more positions and increased accuracy in tough GNSS environments
- ▶ Compatible with existing and planned GNSS constellations to maximize investment
- ▶ Flexible software options to collect, process, and manage data with simple, connected workflows



## PHYSICAL DIMENSIONS

Geo 7X handheld (H x W x D) ..... 234 mm x 99 mm x 56 mm  
(9.2 in x 3.9 in x 2.2 in)

Geo 7X handheld with rangefinder ..... 1080 g

## GNSS, ORIENTATION, AND DISTANCE<sup>1</sup>

GNSS sensor ..... L1/L2 GNSS receiver and antenna

Chipset ..... Trimble Maxwell™ 6 (up to 220 channels)

Systems ..... GPS, GLONASS, Galileo, BeiDou, QZSS

SBAS ..... WAAS, EGNOS, MSAS, GAGAN, SBAS+

Floodlight ..... Yes

Receiver protocols ..... NMEA, TSIP2

Update rate ..... 1 Hz

Time to first fix ..... < 45 seconds (typically)

Real-time correction protocols ..... RTCM2.x/RTCM3.x/CMR+/CMRx

Real-time Centimeter mode accuracy<sup>2</sup>

Horizontal ..... 1 cm + 1 ppm HRMS

Vertical ..... 1.5 cm + 2 ppm VRMS

Postprocessed Centimeter mode accuracy<sup>2</sup>

Horizontal ..... 1 cm + 1 ppm HRMS

Vertical ..... 1.5 cm + 1 ppm VRMS

H-Star™ accuracy (real-time or postprocessed) ..... 10 cm + 1 ppm HRMS

Code DGNSS accuracy (real-time) ..... 75 cm + 1 ppm HRMS

Code DGNSS accuracy (postprocessed) ..... 50 cm + 1 ppm HRMS

SBAS accuracy ..... <100 cm

CenterPoint® RTX (via cellular)<sup>1</sup>

Horizontal ..... 4 cm HRMS

Vertical ..... 10 cm VRMS

FieldPoint RTX™ (via cellular)<sup>1</sup> ..... 10 cm HRMS

RangePoint™ RTX (via cellular)<sup>1</sup> ..... 30 cm HRMS

ViewPoint RTX™ (via cellular)<sup>1</sup> ..... 50 cm HRMS

Orientation sensors<sup>5</sup> ..... 3-axis gyro, magnetometer, accelerometer

Heading accuracy ..... ±1.5°

Inclination accuracy ..... ±0.5°

Roll accuracy ..... ±0.5°

Distance sensor ..... Laser rangefinder module

Communication protocols ..... NMEA or Trimble proprietary

Passive range ..... Up to 120 m

Reflective range ..... Up to 200 m

Accuracy<sup>3</sup> ..... ±0.05 m

Range precision ..... 0.01 m

## NETWORK AND WIRELESS CONNECTIVITY

GSM/GPRS/EDGE ..... 850 / 900 / 1800 / 1900 MHz

UMTS/HSPA+ ..... 800 / 850 / 900 / 1900 / 2100 MHz

CDMA/EV-DO Rev. A ..... 800 / 1900 MHz (Verizon certified)

Wi-Fi ..... 802.11b/g

Bluetooth profiles ..... BT 2.0 +EDR (SPP, OPP, FTP, PAN, A2DP, DUN, HID)

## POWER AND BATTERY<sup>4</sup>

Type ..... Rechargeable, removable Li-Ion

Capacity ..... 11.1V 2,500 mAh

Charge time ..... < 4 hours (typical)

Real time DGNSS usage (via integrated 3G/3.5G) ..... Up to 7 hours

Real time DGNSS usage (via Bluetooth) ..... Up to 9.5 hours

Autonomous GNSS usage ..... Up to 10.5 hours

Non-GNSS use ..... Up to 24 hours

Standby ..... Up to 50 days

## SYSTEM CPU, MEMORY, AND CAMERA

CPU ..... Texas Instruments DM3730 1 GHz + GPU

Memory ..... 4 GB user memory + SD slot (up to 32 GB), 256 MB RAM

Camera ..... 5 MP

## DISPLAY AND TOUCH PANEL

Display ..... 4.2" VGA (640 x 480) LED transfective

Touch panel ..... Resistive touch panel with polarized light filter

Brightness ..... 280 cd/m<sup>2</sup>

## OS

Microsoft® Windows® Embedded Handheld version 6.5 Professional.  
English (U.S.), Chinese (Simplified), Chinese (Traditional), French, German, Italian,  
Japanese, Korean, Spanish, Portuguese (Brazil), Russian.

## SYSTEM REQUIREMENTS

Syncing with a PC requires Windows 7; Windows Vista; or Windows XP Home or Professional with Service Pack 3 or later. Some field applications and services require mobile internet access.

## ENVIRONMENTAL USE

Operating ambient temperature ..... -4° to 140° F (-20° to 60° C)

Storage temperature ..... -22° to 158° F (-30° to 70° C)

Relative humidity ..... 95% non-condensing

Maximum operating altitude ..... 29,000 ft (9,000 m)

Maximum storage altitude ..... 40,000 ft (12,000 m)

Water/dust ingress ..... IP65

Functional shock ..... MIL-STD 810G Method 516.6 Procedure I

Drop ..... 4 ft (1.22 m)

Vibration ..... MIL-STD 810 G Method 514.6 Procedure I

## SOFTWARE COMPATIBILITY

Please refer to the **Product Compatibility** list.  
([www.trimble.com/mappingGIS/productcompatibility](http://www.trimble.com/mappingGIS/productcompatibility))

1 Accuracy and reliability may be subject to anomalies due to multipath, obstructions, satellite geometry, and atmospheric conditions. Always follow recommended GNSS data collection practices. Specified Centimeter accuracy can normally be achieved for baselines of 30 km or less. Specified H-Star accuracy can normally be achieved for baseline lengths of 100 km or less. Centimeter and H-Star accuracy is typically achieved within 2 minutes. CenterPoint RTX accuracy is typically achieved within 5 minutes in select regions, and within 30 minutes worldwide. FieldPoint RTX accuracy is typically achieved within 5 minutes in select regions, and within 15 minutes worldwide. RangePoint RTX and ViewPoint RTX accuracy is typically achieved within 5 minutes.

2 Stated accuracy is with Trimble Zephyr™ Model 2 GNSS antenna. Requires the Geo 7 series Centimeter Option.

3 1-sigma. @ 20 C. to Kodak Grey card at 50 m.

4 Actual run time will vary with conditions and environment of use.

5 1-sigma. Accuracy and reliability may be subject to anomalies due to sensor calibration quality, temperature, and presence of local magnetic disturbances. Always follow recommended sensor calibration and operation practices.

Specifications subject to change without notice.



Contact your local Trimble Authorized Distribution Partner for more information

### NORTH AMERICA

Trimble Navigation Limited  
10368 Westmoor Drive  
Westminster CO 80021  
USA

### EUROPE

Trimble Germany GmbH  
Am Prime Parc 11  
65479 Raunheim  
GERMANY

### ASIA-PACIFIC

Trimble Navigation  
Singapore Pty Limited  
80 Marine Parade Road  
#22-06, Parkway Parade  
Singapore 449269  
Singapore

